# **ESCORTS**





#### SPECIFICATIONS

# RATED CAPACITY

15 Tonne at 1.6 m radius 2.0 Tonne at 9.9 m radius

## **ENGINE**

Make & Model Escorts AE 4.312C-3A four cylinder, water

cooled diesel engine, developing 49.5 HP

@ 2200 RPM or equivalent

\*500 hrs service interval available in escorts engine.

# C TRANSMISSION

Drive 2 Wheel drive

Type Heavy duty transmission developed

especially for crane application. Constant mesh gearbox coupled with straight drive axle. Eight forward and two reverse speeds with high/low

selector lever

Creep Speed 1.9 km/hr, ideal for crane operation

Max. Speed 29 km/hr. (unladen)

Clutch Heavy duty clutch, wire woven,

asbestos free

## STEERING

Type Articulated power steering, hydraulically

controlled through 2 double acting jacks

Articulation Up to 56° Turning Radius 6.75 m

#### **BRAKES**

Front Wheel Pneumatic assisted hydraulic brakes

Rear Wheel Disc brakes actuated through a slave

cylinder

Parking Hand control valve operated, Air assisted

Hydraulic parking brakes at all wheels

(Standard models)

Hand control valve operated, Air assisted Parking brakes at Front wheels (with front

Air brake models)

#### **O** TYRES

Front 11.00 X 20 -16 PR (4 nos.), inflation

pressure 110 - 115 PSI

Rear 13.00 X 24 -12 PR (2 nos.), inflation

pressure 35 PSI. Water ballasted

#### TRACK

Front 1980 mm Rear 1680 mm

#### BOOM

Telescoping 3 parts hydraulically powered & fully

synchronized

Type Slotted boom with rope compensation

Derricking Through double acting jacks

## HOIST MECHANISM

Hoist Hydraulic winch. Six falls (Winch

capacity 12 T). Rope dia 13 mm

# HYDRAULIC SYSTEM

Pump Vane type hydraulic pump

Control Valve 4 spool control valve with built in

pressure relief valve and precision

control

Hydraulic Filter Suction line has a 100 mesh in-line

strainer while return line has 25

microns full flow filter

## **ELECTRICAL SYSTEM**

Type 12V Single battery, Negative earth

## CAPACITIES

Fuel Tank 38 ltrs. Hydraulic Tank 65 ltrs.

# OVERALL DIMENSIONS

 Length
 11900 mm

 Width
 2550 mm

 Height
 3100 mm

# DPERATING WEIGHT (KG)

Gross Vehicle 11700 kg Weight

## .

#### SAFETY SYSTEM


- Rope compensation for auto leveling
- Overload audio warning system
- · Hose protection fallure device
- · Safety brakes on hoist
- · Cylinder guard for protection
- System Low air pressure warning buzzer

## STANDARD ACCESSORIES

- · All Weather Cabin
- Lift Cylinder Guard
- Turn & Reverse Lamp
- · Front Bumper
- Rear View Mirror
- · Reflectors

#### OPTIONAL ACCESSORIES

- Fly Jib Tool Box
- Spark Arrestor Fire Extinguisher
- Steering Wheel
   Heavy Duty Bumper
- Safe Load Indicator
- 14 x 24 Heavy Duty Tyres
- · Air Brakes on Front Wheel
- Over Hoist & Hydraulic Cutoff Kit



Rated loads are calculated for operation on leveled surface.

#### FEATURES



BOOM

Slotted Boom & Rope Compensation for precision handling & auto leveling of loads.



REAR BRAKES

Disc brakes at the rear for effective braking



TRANSMISSION

Heavy duty straight axle with constant mesh transmission.



HYDRAULIC WINCH OF 12T

Capacity with 6 falls snatch block for precision handling & low maintenance.



CABIN

Ergonomically designed spacious cabin with modern dashboard for utmost operator comfort and operation.




ENGINE

Escorts engine BS-III (CEV compliant) high on power/torque & low on fuel consumption & maintenance.











Escorts Kubota Limited (Formerly Escorts Limited) Construction Equipment Plot No. 219, Sector- 58, Ballabhgarh- 121 004, Faridabad, Haryana (INDIA) Tel.: 0129-2306574/2306598/2306571

Fax: 0129-2306572 Website: www.escortsgroup.com



Authorised Dealer