



Spelub 15W40 (API-CH-4)



Performance Standards: Meets

- API-CF 4 / SL / CF 4
- MB 228.3
- VOLVO VDS-2
- ACEA E3-96

Specification:

Properties	15W40 CH-4
Specific Gravity 20°C Kg/1,ASTM D4052	0.871
Kinematic Viscosity, @100°C,ASTM D445,cSt.	13.5 – 15.5
Kinematic Viscosity,@40°C,ASTM D445,cSt.	98 -105
Viscosity Index,ASTM D2270,Min.	>135
Flash Point,(COC),°C,ASTM D92,Min.	220
Pour Point,°C,ASTM D97	-27
Sulphated Ash,%wt,ASTM D874,Max,	1.03
TBN,mg KOH/g,ASTM D2896,Min.	9 - 11

Available Pack Size: 210 Litre.



For additional Support and technical details contact Lubgraf.



Phone: (+91) 792584 1912 / 2970 2511

Email: marketing@lspl.in / info@lspl.in

Website : www.lubgrafsynoils.com

The above information is provided to best of knowledge. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS.

Material Safety Data Sheets (MSDS) are available by emailing us or contacting your sales representative. Always consult the appropriate MSDS before using any of our products.

Neither Lubgraf Synoils Private Limited nor any of its affiliates makes any warranties, express, implies or accepts any liability in connection with this product, related information or its use. The user alone must finally determine suitability of any information or products for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. The information and the products are for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process.



LUBGRAF SYN^oILS PRIVATE LIMITED

PLOT-3405/3406, G.I.D.C., PHASE-IV, VATVA, AHMEDABAD-382445.
PH. 079-40085726-30 25841912-0726 FAX : 079-40085728 E-mail : info@lspl.in