



Spelub EP-2

Multi-purpose Range of Complex Greases



Spelub-EP-2 is formulated and is used in variety of applications and industries to provide protection for components like bearing, roller bearing, gears, cams, bushings, pins and others. Spelub-EP-2 grease offer range of benefits like cost saving, longer tool life, protection against rust and low downtime. Spelub EP greases are available in 000, 00, 0, 1 and 2 N.L.G.I. grades.

Advantages and Benefits:

Features	Benefits
<i>Extreme Pressure Properties</i>	Addition of multiple additives ensures that Spelub-EP-2 provides protection even in medium load conditions.
<i>Excellent Mechanical Stability</i>	Performs in range of high and low speed applications.
<i>Water Resistance</i>	Spelub-EP-2 grease has good resistance to water and moisture. Does not wash away and protects the mechanical parts in moisture conditions.
<i>Anti-rust and Anti-corrosion Properties</i>	Mechanical parts lubricated with Spelub-EP-2 grease are protected against rust and corrosion that extend the service life.
<i>Excellent Adhesion</i>	The overall stability of grease is increased. It does not leak easily. Increases the re-lubrication intervals.
<i>Anti-Wear Properties</i>	Provides the mechanical parts against wear to maximize the service life of the parts and machine.

Typical Properties:

	Spelub-EP-2
Appearance	Brownish
Base Oil	Highly Refined Mineral Oil
Thickener	Complex Soap
Operating Temperature	-10°C to 180°C
Penetration	265 to 295
Evaporation Loss	< 3%
Copper Corrosion	<1a.

Application: Spelub-EP-2 has various applications from centralized lubrication system to manual application. Mechanical parts located in high temperature zones and loads.

Packing: Available in 1kg, 5kg containers and 180 kg barrel.



For additional Support and technical details contact Lubgraf.

Phone: (+91) 792584 1912 / 2970 2511

Email: marketing@lspl.in / info@lspl.in

Website: www.lubgrafsynoids.com

The above information is provided to best of knowledge. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS.

Material Safety Data Sheets (MSDS) are available by emailing us or contacting your sales representative. Always consult the appropriate MSDS before using any of our products.

Neither Lubgraf Synoids Private Limited nor any of its affiliates makes any warranties, express, implies or accepts any liability in connection with this product, related information or its use. The user alone must finally determine suitability of any information or products for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. The information and the products are for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process.



LUBGRAF SYN OILS PRIVATE LIMITED

PLOT-3405/3406, G.I.D.C., PHASE-IV, VATVA, AHMEDABAD-382445.
PH. 079-40085726-30 25841912-0726 FAX : 079-40085728 E-mail : info@lspl.in