



Spelub OG-10(A)

Spelub OG-10(A) is mineral base open gear compound with high percentage of solid lubricant MOS₂ for application of girth gears and is used for girth gears in cement, sugar, paper, steel, power and chemical industries as lubricant.

The Aluminum-Complex base used as thickener gives superior lubrication, excellent reversibility and higher temperature resistance. The additive package contains solid lubricants, tackifier, anti-oxidant, E.P. agents, corrosion inhibitors and additives for better water resistance.

Advantages:

- Excellent anti-wear and E.P. properties.
- No flashing even at high speeds.
- Free from bitumen and solvents.
- Low contamination of covers.
- Spray intervals can be increased gradually.
- Excellent adhesion on metal surfaces.
- Does not attack on seals of spray equipments
- Good corrosion protection.
- Does not contain components hazardous to health.
- Keeps wear and tear of gear teeth under control.

Typical Properties:

Spelub OG-10(A)	
Color	Black
Thickener	Aluminum-Complex
Worked Penetration (At 25 ⁰ C worked 60 strokes)	400-430
Kinematic Viscosity @40 ⁰ C	>1000 cst
Kinematic Viscosity @100 ⁰ C	>55 cst
Consistency(NLGI)	00
Density	0.98 ± 0.02
Copper corrosion (7 days at Room temp)	Nil
Four Ball test	> 4000N
FZG Test	>12

Application: As lubricant of open girth gears cement plant, coal crushers in power stations, ball mills and palletizing mills in ore mines, direct reduction furnaces in steel mills, open gears on mining shovels (drive/dragline, etc) & gear in sugar, paper mills. Also suitable for the lubrication of slide ways, chains and wire ropes.

Packing: 180 Kg drum.



For additional Support and technical details contact Lubgraf.

Phone: (+91) 792584 1912 / 2584 1075

Email: marketing@lspl.in / info@lspl.in

The above information is provided to best of knowledge. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS.

Material Safety Data Sheets (MSDS) are available by emailing us or contacting your sales representative. Always consult the appropriate MSDS before using any of our products.

Neither Lubgraf Synoils Private Limited nor any of its affiliates makes any warranties, express, implies or accepts any liability in connection with this product, related information or its use. The user alone must finally determine suitability of any information or products for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. The information and the products are for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process.



LUBGRAF SYN OILS PRIVATE LIMITED

PLOT-3405/3406, G.I.D.C., PHASE-IV, VATVA, AHMEDABAD-382445.
PH. 079-40085726-30 25841912-0726 FAX : 079-40085728 E-mail : info@lspl.in