



Spelub-SS-680 HT
(High Temperature Slip Seals Grease)



Spelub-SS Grease 680 HT is a metal complex thickener high thermal stability grease with extreme pressure withstanding capabilities. It is specially formulated to provide protection against extreme temperature mechanical wear & tear. It has excellent pump ability. Spelub-SS-680 HT is recommended high mechanical and share stability. Thick Film and EP additives achieve and absorb high and shock load. Excellent adhesion properties, anti-wear properties assure reliable operation.

BENEFITS:

- Kiln & Cooler Slip Seals Application
- Excellent Sealing Invariability
- Withstand under Temperature
- Excellent anti-wear properties
- Extreme Thermal Stability

Characteristics	Test Method	Unit	Spelub-SS Grease 680 HT
Appearance	Visual	-	Smooth
Colour	Visual	-	Brown
Base [Thickener]	-	-	Metal Complex
Base Oil	-	-	Mineral Oil
Base Oil Viscosity	ASTM D-445	cSt	720- 700
Flash Point	ASTM D-99	°C	275
NLGI Grade	-	-	# 1/ 2
Worked Penetration	ASTM D-217	0.1 mm	310 - 330
Dropping Point	ASTM D-2265	°C	≥ 280
Copper Strip Corrosion Test	ASTM D-4048	rating	1a
Operating Temperature Range	-	°C	-20 +260°C

Packing: Available in 20kg and 180 kg barrel.



additional Support and technical details contact Lubgraf.

Phone: (+91) 792584 1912 / 2970 2511

Email: marketing@lspl.in / info@lspl.in

Website : www.lubgrafsynoils.com



The above information is provided to best of knowledge. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESS OR IMPLIED, REGARDING ITS CORRECTNESS.

Material Safety Data Sheets (MSDS) are available by emailing us or contacting your sales representative. Always consult the appropriate MSDS before using any of our products.

Neither Lubgraf Synoils Private Limited nor any of its affiliates makes any warranties, express, implies or accepts any liability in connection with this product, related information or its use. The user alone must finally determine suitability of any information or products for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. The information and the products are for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process.



LUBGRAF SYN OILS PRIVATE LIMITED

PLOT-3405/3406, G.I.D.C., PHASE-IV, VATVA, AHMEDABAD-382445.
PH. 079-40085726-30 25841912-0726 FAX : 079-40085728 E-mail : info@lspl.in